

**SUPERSOL**

Solventli Yağ Giderici

Solvent-based Degreasing Agent

**1. Fiziksel ve Kimyasal Özellikler**

<b>Fiziksel durum</b>	Sıvı
<b>Renk</b>	Viskoz-Opak
<b>Koku</b>	Karakteristik
<b>pH(%5)</b>	8,0 ± 0,5
<b>Yoğunluk(15°C)(g/ml)</b>	1,0 ± 0,1
<b>Kimyasal Yapı</b>	Muhtelif ester ve emülgatörlerin sinerjetik karışımı
<b>İyonik Yapı</b>	Nonyonik

**2. Açıklama**

- ☒ SUPERSOL emülsiyeye kabiliyeti yüksek, özel solventlerle hazırlanmış çok güçlü, tatbikatı kolay bir yağ gidericidir.
- ☒ Bünyesinde bulunan özel yüzey aktif maddeler sayesinde yüzey gerilimi minimize ederek, derideki yağın emülsiyeye edilmesini sağlar.
- ☒ Sert sulara karşı dayanıklıdır.
- ☒ Ham derinin yağ durumuna göre % 3 - 7 oranında kullanılır.

**3. Uygulama****Küçükbaş koyun derilerinde;**

- ☒ Susuz ısıtılmış dolapta ( 35-38°C ) % 3-7SUPERSOL. 60 dakika çalış.
- ☒ Yıkama % 100 su ile ( 35-38°C ) % 3 Tuz ilave 30 dakika çevir.( En az iki defa )
- ☒ Banyo berrak olunca boşalt.

**Kürk süet imalatında;****1. banyo Flotte oranı 1/10 (35 - 38 °C)**

- ☒ 4 - 8 g/L SUPERSOL
- ☒ 7-8 g/L tuz ilavesi ile 30 – 45 dakika çalış – süz.

**2. banyo Flotte oranı 1/10 (35 - 38 °C)**

- ☒ 2-5 gr/L SUPERSOL 60-90 dak.- süz.

NOT: Yağlı derilerde verilen değerlerin üst limitlerinin kullanılması önerilir.

**1. Physical And Chemical Properties**

<b>Physical state</b>	Liquid
<b>Color</b>	Viscous-opaque
<b>Odor</b>	Characteristic
<b>pH(%5)</b>	8,0 ± 0,5
<b>Density(15°C)(g/ml)</b>	1,0 ± 0,1
<b>Chemical Properties</b>	Mixture of various esters and surface active substances
<b>Ionic Properties</b>	Nonionic

**2. Explanation**

- ☒ SUPERSOL is a very powerful, easy to apply degreaser which is prepared with special solvents.
- ☒ Via containing special surfactants, it minimizes surface tension and provides emulsification of dubbin.
- ☒ Resistant to hard water.
- ☒ It is used 3 - 7% as per fatness of dubbin.

**3. Application****Degreasing on the leathers of small cattle;**

- ☒ SUPERSOL %3 - 7 (dry 35 - 38 °C) 60 min.
- ☒ Washing 100 % water (35 - 38 °C) + %3 salt, 30 min. (at least twice)
- ☒ Drain after the bath is clear.

**Degreasing on the operation of fur and suet;****1. Bath Flotte rate 1/10 (35 - 38°C)**

- ☒ 2 - 5g/L SUPERSOL
- ☒ 7-8g/L salt addition, 30-45 min. Must be filtered.

**2. Bath Flotte rate 1/10 (35 - 38 °C)**

- ☒ 2 - 5 g/L SUPERSOL 60-9min. Must be filtered.

NOTE: It is recommended to use the upper limits of the values of given on the oily leathers

**BOSTANCI KİMYA SAN. VE TİC. LTD. ŞTİ**

İstanbul Tuzla Kimya Sanayicileri OSB Melek Aras Bul.  
Analitik Cad. No: 3 Tuzla / İSTANBUL

☎ : +90 216 593 05 67  
☎ : +90 216 593 05 69

☎ info@bostancikimya.com.tr  
☎ www.bostancikimya.com.tr

**SUPERSOL**

Solventli Yağ Giderici

*Solvent-based Degreasing Agent***4. Raf Ömrü**

Orijinal ambalajında, 10°C ile 40°C arasında depolanmalıdır. Raf ömrü 12 aydır.

**4. Shelf Life**

*It should be stored between 10°C and 40°C in its original package. Shelf life is 12 months.*

**5. Paketleme**

60L'lik veya 120L'lik plastik bidon.

**5. Packaging**

*60L or 120L of plastic drums.*

**BOSTANCI KİMYA SAN. VE TİC. LTD. ŞTİ**

İstanbul Tuzla Kimya Sanayicileri OSB Melek Aras Bul.  
Analitik Cad. No: 3 Tuzla / İSTANBUL

☎ : +90 216 593 05 67  
☎ : +90 216 593 05 69

✉ [info@bostancikimya.com.tr](mailto:info@bostancikimya.com.tr)  
🌐 [www.bostancikimya.com.tr](http://www.bostancikimya.com.tr)